
ACB1600 Specifications

| Frame | 20 mm x 20 mm x 1.6 mm Welded Steel Tube |
|-------------------------|--|
| Mesh | 25 mm x 25 mm x 3 mm Welded Mesh - Welded to Frame |
| Cage Depth | 600 mm 0D - 580 mm ID |
| Cage Width | 595 mm OD - 555 mm wide ID |
| Cage Length | 1590 mm OD, 1570 mm ID |
| Fixing Plate | 80 x 35mm plate with slotted holes to suit 8mmØ fixings to wall and ground |
| Mounting Brackets | 80 x 35mm Mounting Brackets supplied to provide 55mm clearance for pipework Cage can be installed with or without mounting brackets |
| Cage Safety | Corners are 90 mm radius to minimise personal injury |
| Assembly Required | Units are made up of the following parts (see diagram) #1 - Front Panel (Removable) #2 - Side Panel #3 - Side Panel with Access #4 - Access Panel (Removable) with Padlock Tab #5 - End Panel (Removable) #6 - Mounting Brackets |
| Lockable | Access Door has a Welded Tab if Padlock is required |
| Assembly Fixings | All Fixings supplied - M6 tamper proof Torx bolts, washers and tool |
| Optional End Panel | Available - Part No EPB0001 |
| Optional Joiner Bracket | Available to join and extend multiple cages - Part No JBB0001 |
| Coating | Two stage protection with Zinc Plating and Black Powder Coating |
| | |





AVANTAGE

© 2023 Avantage Australia reserves the right to alter products and specifications without notice and does not accept responsibility for possible errors and omissions in published documentation. Date: 16/04/2023 Document: Avantage Airshield Cages ACB1600 Spec Sheet Version Number: V2

A: 74 Scanlon Drive, Epping VIC 3074 T: 03 9989 5850 W: avantageaustralia.com.au E: sales@avantageaustralia.com.au